

#GR115

HONDA FOREMAN 400 SUZUKI EIGER 400

TO MOUNT THE MAIN BRACKET TO THE SUZUKI EIGER YOU MUST LOOSEN THE TWO 8MM BOLTS THAT HOLD THE 2WD&4WD SWITCH ON THE BARS. PLACE THE CLIP BEHIND THE CABLE THEN PROCEED TO MOUNT THE BRACKET IN PLACE, ONCE THIS IS DONE TIGHTEN THE SWITCH BOLTS.

- 2=1/4 NUTS-A
 - 4=1/4 LOCK NUTS-B
 - 2=1/4 LOCK WASHERS-C
 - 6=1/4 SAE WASHERS-D
 - 2=1/4X2 BOLTS-E
 - 2=1/4X1 SQUARE U-BOLTS-F
 - 2=7/16 LOCK NUTS-G
 - 4=7/16 SAE WASHERS-H
 - 2=5/16X1 1/4 BOLTS-I
 - 4=5/16 SAE WASHERS-J
 - 2=7/16X2 1/4 BOLTS-K
 - 2=5/16 LOCK NUTS-L
 - 6=1/4 ROD CAPS-M
 - 2=1" PLUGS-N
 - 1= ALUMIN. WASHERS SLOTS-O
 - 2=3/16X1 1/4X7/8 ROUND CLIPS-P
 - 1=GR BRACKET L SHAPE-Q
- 1= 1" TUB. 19 LONG
2=1520
1=MAIN BRACKET
- PACK IN BOX,

