

4=1/4 X 1 LONG YELLOW U-BOLTS-A
 12=1/4 LOCK NUTS-B
 8=#16 TANNER RIVETS-C
 8=5/16 SAE WASHERS-D
 4=1/4 X 2 BOLTS-E
 2=1/8" X 1" CHANNEL IRONS 5" LONG
 WITH ENDS CUT TO A 72° ANGLE.-F



SS157H

KAWASAKI MULE 3000/3010 4X4

EVEN THOUGH THE NEW BOOT GUARDS YOU HAVE PURCHASED WILL COVER MORE THAN THE ORIGINAL PLASTIC GUARDS. BOOTS HAVE BEEN REPORTED TO BE TORN IN SOME CONDITIONS .DUE TO THE TURING RADIUS ON SOME OF THE NEWER ATV'S. THE BOOT PROTECTORS HAVE BEEN MANUFACTURED SMALLER TO ALLOW FOR A TIGHTER TURING RADIUS. SAVANT MFG. (STRONG MADE) DOES NOT WARRANTY AND TORN BOOTS.

THIS IS THE FRONT OF THE SS157H THIS IS WHAT YOU WILL SEE ONCE IT HAS BEEN MOUNTED TO THE A-ARM.

THIS END WILL FACE THE INSIDE OF THE RIM ONCE IT HAS BEEN MOUNTED.

